

Selvol[™] Polyvinyl Alcohol 24-203 Solution

Specifications		Limits
Hydrolysis, mole%	Min.	88.00 +/- 1.00
Solution Viscosity, cP		775.00 +/- 525.00
Solution Solids, wt%	Max.	24.00 +/- 1.00
Total Organic Volatiles, wt%	Max.	1.00
Methanol, wt%	Max.	0.90
Ash - ISE, wt%	Max.	0.90
Solution pH		5.50 +/- 1.00

SALES SPECIFICATION

Note:

Ash, hydrolysis, methanol and total organic volatiles are based on the polyvinyl alcohol from which the solution was prepared. pH solids and viscosity are based on the solution.

North America Sekisui Specialty Chemicals America, LLC 1501 West LBJ Freeway, Suite 530 Dallas, TX 75234 USA Tel: +1-972-277-2900 Fax: +1-972-277-2907

Europe

Sekisui Specialty Chemicals Europe, S.L. Ctra. N-340, Km 1157 Apartado de Correos 1388 43080 Tarragona, Spain Tel: + 34-977-549-899 Fax: + 34-977-544-982

www.Sekisui-sc.com www.Selvol.com

SSC-24-203 Revision 3: 7/2012

This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should therefore not be construed as guaranteeing specific properties of the products described or their suitability for a particular application or purpose. Any existing industrial property rights must be observed. The quality of our products is guaranteed under our General Conditions of Sale.