

## Selvol<sup>™</sup>Polyvinyl Alcohol 502

## **SALES SPECIFICATION**

Specifications		Limits
Hydrolysis, mole%		88.00 +/- 1.00
4% Solution Viscosity, cP <sup>1</sup>		3.35 +/- 0.35
Total Volatiles, wt% <sup>2</sup>	Max.	5.00
Total Organic Volatiles, wt%	Max.	1.00
Methanol, wt%	Max.	0.90
Ash - ISE, wt% <sup>3</sup>	Max.	0.90
4% Solution pH <sup>4</sup>		5.50 +/- 1.00

<sup>&</sup>lt;sup>1</sup> 4% aqueous solution, 20℃

North America Sekisui Specialty Chemicals America, LLC 1501 West LBJ Freeway, Suite 530 Dallas, TX 75234 USA

Tel: +1-972-277-2900 Fax: +1-972-277-2907

## **Europe**

Sekisui Specialty Chemicals Europe, S.L. Ctra. N-340, Km 1157 Apartado de Correos 1388 43080 Tarragona, Spain

Tel: + 34-977-549-899 Fax: + 34-977-544-982

www.Sekisui-sc.com www.Selvol.com

SSC502 Revision 3: 7/2012

This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should therefore not be construed as guaranteeing specific properties of the products described or their suitability for a particular application or purpose. Any existing industrial property rights must be observed. The quality of our products is guaranteed under our General Conditions of Sale.

<sup>&</sup>lt;sup>2</sup> Total volatiles including water

As % Na<sub>2</sub>0, corrected volatiles

<sup>&</sup>lt;sup>4</sup> 4% aqueous solution