

Selvol™ Ultalux® AD

SALES SPECIFICATION

Specifications		Limits
8% Solution Viscosity, cP		30.0 +/- 15.0
Total Volatiles, wt% ¹	Max.	5.0
Total Organic Volatiles, wt%		< 3.0
Ash - ISE, wt% ²	Max.	3.0
4% Solution pH ³		11.5 +/- 0.5

¹ Total volatiles including water

² As % Na₂O, corrected volatiles

³ 4% aqueous solution

Other Data Properties	Value
Heavy Metal Content, mg/kg ⁴	≤10 mg/kg
15% Solution Viscosity, cP	500 ± 50

⁴ Verified biannually by a third party lab using USP/NF Method for heavy metals

INCI Name: Vinyl Amine/Vinyl Alcohol Copolymer

North America

Sekisui Specialty Chemicals America, LLC
 1501 West LBJ Freeway, Suite 530
 Dallas, TX 75234 USA
 Tel: +1-972-277-2900
 Fax: +1-972-277-2907

Europe

Sekisui Specialty Chemicals Europe, S.L.
 Ctra. N-340, Km 1157
 Apartado de Correos 1388
 43080 Tarragona, Spain
 Tel: + 34-977-549-899
 Fax: + 34-977-544-982

www.Sekisui-sc.com

SSCUltalux AD
 11/2013_r01

This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should therefore not be construed as guaranteeing specific properties of the products described or their suitability for a particular application or purpose. Any existing industrial property rights must be observed. The quality of our products is guaranteed under our General Conditions of Sale.