

Selvol™ Ultalux® SC

ESPECIFICACIONES COMERCIALES

Especificaciones		Límites
Viscosidad (Solución 8%), cP		80.0 +/- 40.0
Volátiles totales, %Peso ¹	Max.	5.0
Compuestos Orgánicos Volátiles, %Peso		< 3.0
Cenizas - ISE, %Peso ²	Max.	1.2
pH (Solución 4%) ³		8.0 +/- 2.0

¹ Volátiles totales incluida el agua

² Expresado como Na₂O

³ Solución acuosa al 4%

Otras Propiedades	Valor
Contenido en Metales Pesados, mg/kg ⁴	≤10 mg/kg
Viscosidad (Solución 15%), cP	1500 ± 100

⁴Verificado semestralmente por un laboratorio independiente usando un método USP/NF para Metales Pesados.

Nombre INCI: VP/Vinyl Alcohol Copolymer

North America

Sekisui Specialty Chemicals America, LLC
 1501 West LBJ Freeway, Suite 530
 Dallas, TX 75234 USA
 Tel: +1-972-277-2900
 Fax: +1-972-277-2907

Europe

Sekisui Specialty Chemicals Europe, S.L.
 Ctra. N-340, Km 1157
 Apartado de Correos 1388
 43080 Tarragona, Spain
 Tel: + 34-977-549-899
 Fax: + 34-977-544-982

www.Sekisui-sc.com

SSCUltalux SC
 11/2013_r01

This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should therefore not be construed as guaranteeing specific properties of the products described or their suitability for a particular application or purpose. Any existing industrial property rights must be observed. The quality of our products is guaranteed under our General Conditions of Sale.