

### Section 1 - PRODUCT AND COMPANY IDENTIFICATION

**Material Name**

SELVOL™ Polyvinyl alcohol, 5-30% solutions

**Trade Names**

The following specific grades are covered by this SDS: 09-425, 12-205, 12-523, 21-205, 24-203, 09-523

**Synonyms**

Polyvinyl alcohol, PVA

**Chemical Family**

ACETIC ACID ETHENYL ESTER, POLYMER WITH ETHENOL.

**Product Use**

Intermediate, surfactant, adhesives, Food/feedstuff additives, Packaging materials, Auxiliary for leather, Auxiliary for textile.

**Restrictions on Use**

None known.

**Details of the supplier of the safety data sheet**

Sekisui Specialty Chemicals America, LLC  
1501 LBJ Freeway, Suite 530  
Dallas, TX 75234

**Emergency Phone Numbers:**

In USA: CHEMTREC 800-424-9300

Outside USA: CHEMTREC 703-527-3887 (collect calls accepted)

Phone: +1-972-277-2900

www.sekisui-sc.com

### Section 2 - HAZARDS IDENTIFICATION

**Classification in accordance with paragraph (d) of 29 CFR 1910.1200.**

Skin Sensitization - Category 1A

**GHS Label Elements**

**Symbol(s)**



**Signal Word**

Warning

**Hazard Statement(s)**

May cause an allergic skin reaction.

**Precautionary Statement(s)**

**Prevention**

Avoid breathing dust/fume/gas/mist/vapours/spray.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves.



## Safety Data Sheet

Material Name: SELVOL™ Polyvinyl alcohol, 5-30% solutions

SDS ID: SSC10004

### Response

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Specific treatment (see label).

### Storage

None needed according to classification criteria.

### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
7732-18-5	Water	70.0-95.0
25213-24-5	Acetic acid ethenyl ester, polymer with ethenol	5.0-30.0
127-09-3	Sodium acetate	0.01-0.1
79-20-9	Methyl acetate	0.001-0.1
67-56-1	Methyl alcohol	0.001-0.1
55965-84-9	5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone	0.0038

## Section 4 - FIRST AID MEASURES

### Description of Necessary Measures

Wash thoroughly after handling.

### Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

### Skin

Wash with plenty of soap and water. If skin irritation or rash occurs, seek medical advice/attention. Wash contaminated clothing before reuse.

### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

### Ingestion

If a large amount is swallowed, get medical attention.

### Most Important Symptoms/Effects

#### Acute

May cause an allergic skin reaction.

#### Delayed

May cause an allergic skin reaction.

### Indication of any immediate medical attention and special treatment needed



## Safety Data Sheet

Material Name: SELVOL™ Polyvinyl alcohol, 5-30% solutions

SDS ID: SSC10004

Treat symptomatically and supportively.

### Note to Physicians

Treat symptomatically and supportively.

## Section 5 - FIRE FIGHTING MEASURES

### Extinguishing Media

#### Suitable Extinguishing Media

The product itself does not burn in solution. dry polymer: Use dry chemical, carbon dioxide, alcohol-resistant foam or water spray.

#### Unsuitable Extinguishing Media

Do not scatter spilled material with high-pressure water streams.

#### Special Hazards Arising from the Chemical

carbon monoxide, carbon dioxide.

#### Fire Fighting Measures

Keep unnecessary people away, isolate hazard area and deny entry. Do not enter confined spaces unless adequately ventilated. Cool containers with water spray until well after the fire is out. Keep away from heat, sparks and flame.

#### Special Protective Equipment and Precautions for Firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

## Section 6 - ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment and Emergency Procedures

Keep unnecessary people away, isolate hazard area and deny entry. The mixture is slippery when wet. Avoid contact with skin and eyes.

### Methods and Materials for Containment and Cleaning Up

Use approved industrial vacuum cleaner for removal. Absorb spillage to prevent material damage. Collect in closed and suitable containers for disposal.

### Environmental Precautions

Prevent environmental discharge consistent with regulatory requirements.

## Section 7 - HANDLING AND STORAGE

### Precautions for Safe Handling

Use only outdoors or in a well-ventilated area. Spilled polymer solution is very slippery. Use care to avoid falls.

Wash thoroughly after handling.

### Conditions for Safe Storage, Including any Incompatibilities

None needed according to classification criteria.

Protect from freezing. Store at room temperature. Store in original container.

### Incompatible Materials

Oxidizing agents, acids, peroxides, perchlorates, nitrates, reactive metals.

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### Component Exposure Limits

Methyl acetate	79-20-9
----------------	---------



## Safety Data Sheet

Material Name: SELVOL™ Polyvinyl alcohol, 5-30% solutions

SDS ID: SSC10004

ACGIH:	200 ppm TWA
	250 ppm STEL
NIOSH:	200 ppm TWA ; 610 mg/m3 TWA
	250 ppm STEL ; 760 mg/m3 STEL
	3100 ppm IDLH (10% LEL )
OSHA (US):	200 ppm TWA ; 610 mg/m3 TWA
Mexico:	200 ppm TWA VLE-PPT ; 610 mg/m3 TWA VLE-PPT
	250 ppm STEL [PPT-CT ] ; 760 mg/m3 STEL [PPT-CT ]
<b>Methyl alcohol</b>	<b>67-56-1</b>
ACGIH:	200 ppm TWA
	250 ppm STEL
	Skin - potential significant contribution to overall exposure by the cutaneous route
NIOSH:	200 ppm TWA ; 260 mg/m3 TWA
	250 ppm STEL ; 325 mg/m3 STEL
	Potential for dermal absorption
	6000 ppm IDLH
Europe:	200 ppm TWA ; 260 mg/m3 TWA
	Possibility of significant uptake through the skin
OSHA (US):	200 ppm TWA ; 260 mg/m3 TWA
Mexico:	200 ppm TWA VLE-PPT ; 260 mg/m3 TWA VLE-PPT
	250 ppm STEL [PPT-CT ] ; 310 mg/m3 STEL [PPT-CT ]
	Skin - potential for cutaneous absorption

### EU - Occupational Exposure (98/24/EC) - Binding Biological Limit Values and Health Surveillance Measures

There are no biological limit values for any of this product's components.

### ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

#### Methyl alcohol (67-56-1)

15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific )

### Engineering Controls



## Safety Data Sheet

Material Name: SELVOL™ Polyvinyl alcohol, 5-30% solutions

SDS ID: SSC10004

Provide local exhaust or process enclosure ventilation system. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

### Individual Protection Measures, such as Personal Protective Equipment

#### Eye/face protection

Wear splash resistant safety goggles. Contact lenses should not be worn.

#### Skin Protection

Wear appropriate chemical resistant clothing. Recommended material type: neoprene.

#### Respiratory Protection

A NIOSH approved air-purifying respirator with an appropriate cartridge or canister may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits.

#### Glove Recommendations

Wear appropriate chemical resistant gloves.

### Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	viscous solution	<b>Physical State</b>	Liquid
<b>Odor</b>	odorless	<b>Color</b>	colorless to yellow
<b>Odor Threshold</b>	Not available	<b>pH</b>	5 - 7.5 , conc: 10%
<b>Melting Point</b>	Not available	<b>Boiling Point</b>	100 C
<b>Boiling Point Range</b>	Not available	<b>Freezing point</b>	Not available
<b>Evaporation Rate</b>	Not available	<b>Flammability (solid, gas)</b>	Not available
<b>Autoignition Temperature</b>	Not available	<b>Flash Point</b>	Not available
<b>Lower Explosive Limit</b>	Not available	<b>Decomposition temperature</b>	Not available
<b>Upper Explosive Limit</b>	Not available	<b>Vapor Pressure</b>	Not available
<b>Vapor Density (air=1)</b>	Not available	<b>Specific Gravity (water=1)</b>	1.02 - 1.05 20 °C
<b>Water Solubility</b>	Not available	<b>Partition coefficient: n-octanol/water</b>	Not available
<b>Viscosity</b>	Not available	<b>Solubility (Other)</b>	Not available
<b>Density</b>	Not available	<b>Molecular Weight</b>	Not available

### Section 10 - STABILITY AND REACTIVITY

#### Reactivity

No hazard expected.

#### Chemical Stability

Stable under normal conditions of use.

#### Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

**Conditions to Avoid**

Protect from freezing.

**Incompatible Materials**

Oxidizing agents, acids, peroxides, perchlorates, nitrates, reactive metals.

**Hazardous decomposition products**

oxides of carbon.

**Section 11 - TOXICOLOGICAL INFORMATION**

**Information on Likely Routes of Exposure**

**Inhalation**

No information on significant adverse effects.

**Skin Contact**

May cause slight irritation. May cause an allergic skin reaction.

**Eye Contact**

May cause slight irritation. viscous polymer solution.

**Ingestion**

May cause gastrointestinal irritation.

**Acute and Chronic Toxicity**

**Component Analysis - LD50/LC50**

The components of this material have been reviewed in various sources and the following selected endpoints are published:

**Water (7732-18-5)**

Oral LD50 Rat >90 mL/kg

**Sodium acetate (127-09-3)**

Oral LD50 Rat 3530 mg/kg

Dermal LD50 Rabbit >10 g/kg

Inhalation LC50 Rat >30 g/m<sup>3</sup> 1 h

**Methyl acetate (79-20-9)**

Oral LD50 Rat >5 g/kg

Dermal LD50 Rabbit >5 g/kg

Inhalation LC50 Rat 16000 ppm 4 h

**Methyl alcohol (67-56-1)**

Oral LD50 Rat 6200 mg/kg

Inhalation LC50 Rat 22500 ppm 8 h

**5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)**

Oral LD50 Rat 53 mg/kg

**Product Toxicity Data**

**Acute Toxicity Estimate**

Dermal	> 2000 mg/kg
Oral	> 2000 mg/kg

**Immediate Effects**

May cause an allergic skin reaction.

**Delayed Effects**

May cause an allergic skin reaction.

**Irritation/Corrosivity Data**

No information on significant adverse effects.



## Safety Data Sheet

Material Name: SELVOL™ Polyvinyl alcohol, 5-30% solutions

SDS ID: SSC10004

**Respiratory Sensitization**

No data available.

**Dermal Sensitization**

May cause an allergic skin reaction.

**Component Carcinogenicity**

None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA

**Germ Cell Mutagenicity**

Ames test found to be negative. No hazard expected.

**Tumorigenic Data**

No data available

**Reproductive Toxicity**

No data available.

**Specific Target Organ Toxicity - Single Exposure**

No target organs identified.

**Specific Target Organ Toxicity - Repeated Exposure**

No target organs identified.

**Aspiration hazard**

No data available.

**Medical Conditions Aggravated by Exposure**

eye disorders, gastrointestinal disorders

**Section 12 - ECOLOGICAL INFORMATION**

**Component Analysis - Aquatic Toxicity**

<b>Acetic acid ethenyl ester, polymer with ethenol</b>	<b>25213-24-5</b>
Fish:	LC50 96 hr Lepomis macrochirus (Bluegill sunfish) 10 g/L; LC50 96 hr Pimephales promelas (Fathead minnow) 40 g/L
Invertebrate:	EC50 48 hr Daphnia magna 8300 mg/L
<b>Sodium acetate</b>	<b>127-09-3</b>
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID
<b>Methyl acetate</b>	<b>79-20-9</b>
Fish:	LC50 96 h Pimephales promelas 295 - 348 mg/L [flow-through ]; LC50 96 h Brachydanio rerio 250 - 350 mg/L [static ]
Algae:	EC50 72 h Desmodesmus subspicatus >120 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna 1026.7 mg/L IUCLID
<b>Methyl alcohol</b>	<b>67-56-1</b>



## Safety Data Sheet

Material Name: SELVOL™ Polyvinyl alcohol, 5-30% solutions

SDS ID: SSC10004

Fish:	LC50 96 h Pimephales promelas 28200 mg/L [flow-through ]; LC50 96 h Pimephales promelas >100 mg/L [static ]; LC50 96 h Oncorhynchus mykiss 19500 - 20700 mg/L [flow-through ]; LC50 96 h Oncorhynchus mykiss 18 - 20 mL/L [static ]; LC50 96 h Lepomis macrochirus 13500 - 17600 mg/L [flow-through ]
-------	---

### Bioaccumulative Potential

Low.

### Biodegradation

90%

### Chemical Oxygen Demand (COD)

Ca. 17000 mgO<sub>2</sub>/g

## Section 13 - DISPOSAL CONSIDERATIONS

### Disposal Methods

Dispose of contents/container in accordance with local/regional/national/international regulations.

### Component Waste Numbers

The U.S. EPA has not published waste numbers for this product's components

## Section 14 - TRANSPORT INFORMATION

### US DOT Information:

UN/NA #: Not Regulated

### TDG Information:

UN#: Not Regulated

## Section 15 - REGULATORY INFORMATION

### U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

<b>Methyl alcohol</b>	<b>67-56-1</b>
SARA 313:	1 % de minimis concentration
CERCLA:	5000 lb final RQ ; 2270 kg final RQ

### SARA Section 311/312 (40 CFR 370 Subparts B and C)

**Acute Health:** Yes **Chronic Health:** No **Fire:** No **Pressure:** No **Reactivity:** No

### U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
<b>Methyl acetate</b>	<b>79-20-9</b>	Yes	Yes	Yes	Yes	Yes
<b>Methyl alcohol</b>	<b>67-56-1</b>	Yes	Yes	Yes	Yes	Yes





## Safety Data Sheet

**Material Name: SELVOL™ Polyvinyl alcohol, 5-30% solutions**

**SDS ID: SSC10004**

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause reproductive/developmental effects

<b>Methyl alcohol</b>	<b>67-56-1</b>
Repro/Dev. Tox	developmental toxicity , 3/16/2012

### Canada Regulations

#### Canadian WHMIS Ingredient Disclosure List (IDL)

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

<b>Methyl acetate</b>	<b>79-20-9</b>
	1 %
<b>Methyl alcohol</b>	<b>67-56-1</b>
	1 %

### Component Analysis - Inventory

#### Water (7732-18-5)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	No	Yes	Yes	Yes	Yes

#### Acetic acid ethenyl ester, polymer with ethenol (25213-24-5)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	No	Yes	Yes	Yes	No	Yes	No	No	Yes	Yes	Yes	Yes

#### Sodium acetate (127-09-3)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes

#### Methyl acetate (79-20-9)



## Safety Data Sheet

**Material Name: SELVOL™ Polyvinyl alcohol, 5-30% solutions**

**SDS ID: SSC10004**

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	No	Yes	Yes	Yes	Yes

**Methyl alcohol (67-56-1)**

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	No	Yes	Yes	Yes	Yes

**5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)**

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
No	DSL	No	No	Yes	Yes	No	Yes	No	No	Yes	Yes	No	Yes

**Section 16 - OTHER INFORMATION**

**HMIS Rating**

Health: 0 Fire: 1 Reactivity: Not available

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe \* = Chronic hazard

**NFPA Ratings**

Health: 0 Fire: 1 Reactivity: Not available

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

**Summary of Changes**

Updated SDS: 3/22/2017

**Key / Legend**

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA - California/Massachusetts/Minnesota/New Jersey/Pennsylvania\*; CAS - Chemical Abstracts Service; CFR - Code of Federal Regulations (US); CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EC - European Commission; EEC - European Economic Community; EIN - European Inventory of (Existing Commercial Chemical Substances); EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; IUCLID - International Uniform Chemical Information Database; JP - Japan; Kow - Octanol/water partition coefficient; KR KECI Annex 1 - Korea Existing



## Safety Data Sheet

Material Name: SELVOL™ Polyvinyl alcohol, 5-30% solutions

SDS ID: SSC10004

Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL); KR KECI Annex 2 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL) , KR - Korea; LD50/LC50 - Lethal Dose/Lethal Concentration; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; MX – Mexico; NDSL – Non-Domestic Substance List (Canada); NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PEL- Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TCCA – Korea Toxic Chemicals Control Act; TDG - Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TW – Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; VLE - Exposure Limit Value (Mexico); WHMIS - Workplace Hazardous Materials Information System (Canada).

### Other Information

#### Disclaimer:

Supplier gives no warranty whatsoever, including the warranties of merchantability or of fitness for a particular purpose. Any product purchased is sold on the assumption the purchaser shall determine the quality and suitability of the product. Supplier expressly disclaims any and all liability for incidental, consequential or any other damages arising out of the use or misuse of this product. No information provided shall be deemed to be a recommendation to use any product in conflict with any existing patent rights